









1. The basket is removable very easy with two locking

3. Optional hydraulic drive wheels for easy movement.

2. Min. width = 0,75m

4. Hydraulic support legs allow a quick and safe set up even on sloping around.

The smallest of them all, but designed with a stroke of genius!

With minimum 0,75m the Junior 12 is small enough to fit through standard doors. The set up is uncomplicated and needs only minimum space.

Double lifting bars give the boom great stability and make it easy to control.

The basket can be loaded with max. 120 kg in the entire working height area, m ax. 12 m etres. The basket is available

All DENKA LIFTs meet the most stringent safety standards. The electrical and hydraulical systems feature double safety devices, the cylinders have hose break valves and all movements have pressure control valve safety systems.


The telescopic boom is made of steel sections.

The combination of the boom's qualities plus the "2-speedsystem" gives the operator in the basket a stable, safe and functional working place.

The Junior 10/12 is supplied for direct connection to 230 V main supply.



Outrigger cross section



Max. working height	
2	12 m
	11
	10
	9
	8
	7
	6
	5
	4
	3
	2
	1

Standard model	Junior12
Kapazität	
Max. working height A	12,0 m
Max. reach D	6,7 m
Max. load in basket	120 kg
Max. antal personer	1 1
Slew movement cont	cont. 360°
Transport dimension	
Length L	5680 mm
Length L*	4950 mm
Min. Length L (incl. basket rotate	d 180°) 5050 mm
Height H / H*	2100/1840 mm
Max. width B	1400 mm
Min. width B*	750 mm
Net weight standard	985 kg
Telescopic boom	2-stage steel

Min. Width $B^* = 750 mm$ - without hydraulic self drive (otherwise 790mm), axes inserted and with option "removable basket 700mm

STANDARD EQUIPMENT:

- Detachable aluminium basket 900 mm
- 230V power supply
- On/off control 2-speed
- Hydraulic outriggers
 ELCB 30 mA
- Hour counter
- removable light bar

EXTRA ACCESSORIES:

- RAL special colours
- Yellow rotating light
- · Biological oil
- Petrol engine Honda EU30is / 3,0kVA*
 Basket integrated LED light bar
- Removable alu basket 700mm
 Hydraulic self drive*
 increase in weight



D-84323 Massing · Mühlenweg 1 雷 +49 8724 9601-0 · 麻 +49 8724 9601-12 info@rothlehner.de · www.rothlehner.de

This data is a guideline only, Pictures may show special equipment that is not part of the standard equipment we reserve the right to make alterations.